



Heavy duty diesel engine oils - Mineral

DCO SHPD 15W40 SL/CI-4

Description

Performance level

- API SL/CI-4
- ACEA A3/B4
- ACEA E7
- Allison C-4
- MB 228.3
- MAN M 3275
- Volvo VDS-3
- Renault RLD-2
- Renault RLD
- Caterpillar ECF-2
- Caterpillar ECF-1-A
- CES 20076
- CES 20077
- CES 20078
- Deutz DQC III-10
- DDC Oil Category 2
- Global DHD-1
- MTU type 2
- MB 229.1
- Detroit Diesel DDC 93K215
- Mack EO-M Plus
- JASO DH-1
- Voith Class A

Physical properties

Colour	brown	
Density at 20°C	0.868 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	111.5 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15.5 cSt	ASTM D 445
Viscosity Index	147	ASTM D 2270
Viscosity, dynamic (CCS)	4396 cP	ASTM D 5293
Flash point	216 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97

Article number V148431005
Version 1.2, 10-05-2019

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.